



Racecourse Tunnel Black Rubber Floor Mats

KINGTOM is a leading China Racecourse Tunnel Black Rubber Floor Mats manufacturer, supplier and exporter. Racecourse Tunnel Rubber Floor Mats with the function of anti-fatigue, anti-skid mat provides safety, drainage and comfort for horses.

KINGTOM is a professional leader China Racecourse Tunnel Black Rubber Floor Mats manufacturer with high quality and reasonable price. **Racecourse Tunnel Rubber Floor Mats** with the function of anti-fatigue, anti-skid mat provides safety, drainage and comfort for horses. The bottom surface has grooves to allow liquid evacuation and its impact-resistant surface to reduce noise and vibration.

Product Parameter of the Racecourse Tunnel Black Rubber Floor Mats:

- ①Product name: **Racecourse Tunnel Black Rubber Floor Mats**
- ②Material: EPDM NBR Silicon or Can Custom
- ③Logo: Can Custom
- ④Size: Can Custom
- ⑤Can Custom: Black or custom
- ⑥Application: Automotive
- ⑦Certifications: IATF16949 ,ISO14001:2015,ROHS,CMC, etc
- ⑧Delivery: 30 -50days after sample confirmation
- ⑨Sample: 25-30 days
- ⑩Payment: 30% deposit, 70% payment before shipment
- ⑪Package: PE bags, Cartons,Pallet
- ⑫Payment Terms: T/T,L/C and so on.
- ⑬Shipment Way: Vessel,Air,Express etc.

Product Feature AND Application of the **Racecourse Tunnel Black Rubber Floor**

Mats:

Racecourse tunnel rubber mats is durable and fade resistant for long-lasting use. The racetrack design provides an attractive look which can fits in almost any surrounding. The rubber backing is anti slip to hold the mat in place. And the polyethylene fabric absorbs dirt and moisture to keep your floors tidy. The mat cleans easily with a vacuum or it can be shaken out, or spray it with water and let it air dry.

Constructed of 100% recycled rubber from tires

Anti slip recycled rubber backing provides safety

Durable weather-resistant door mat withstands seasonal changes for outdoor use all year long

Fabric surface is stain-resistant and absorbs dirt and moisture to keep your floors tidy

Mat is also flame-retardant

UV-stabilized material resists fading

**Parameters:**

- ① Tensile Strength: $\geq 13\text{Mpa}$
- ② Breaking Elongation: $\geq 300\%$
- ③ Hardness (SHORE A): 65 ± 5 degrees (70 °C x 22h, Compression rate: 25 %)
- ④ Abrasion Loss: $\leq 1.0\text{cm}^3 / 1.61\text{km}$
- ⑤ Bonding Strength Between Rubber Mat And Metal Plate $\geq 5\text{Mpa}$
- ⑥ Acid And Alkaline Resistance: $\geq 70\%$ (20% Concentrated Sulfuric, 20% Sodium Hydroxide, 24 Hours / Room Temperature)
- ⑦ Aging With HoT Air (70°C x .96h) Tensile Strength \leq Decrease 20% Breaking Elongation \leq Decrease 20%, Hardness (SHORE A): Increase Of 8 Degrees Maximum.

